

Digital Communication Systems Engineering with Software-Defined Radio

Di Pu, Alexander M. Wyglinski
Worcester Polytechnic Institute

Lecture 23

Inefficient Spectrum Utilization




Figure : Spectrum Snapshot from 88 MHz to 2686 MHz Measured on July 11, 2008 in Worcester, MA, USA ($N42^{\circ}16.36602$, $W71^{\circ}48.46548$).

S. Pagadarai, R. Rajbanshi, G. J. Minden, A. M. Wyglinski. "Agile Transmission Techniques." in *Cognitive Radio Communications and Networks: Principles and Practice* (A. M. Wyglinski, M. Nekovee, Y. T. Hou (eds.)), Academic Press, 2009.

Waveform Agility Needed

- ▶ The utilization efficiency of “prime” wireless spectrum has been shown to be poor
- ▶ In order to better utilize wireless spectrum, detection of white spaces in licensed bands and hardware reconfigurability are crucial
- ▶ A variant of OFDM named *non-contiguous OFDM* (NC-OFDM) meets the above requirements and supports high data-rates while maintaining acceptable levels of error robustness

Spectral “Divide-and-Conquer”




Figure : An Illustration Showing Utilization of Non-contiguous Regions of Spectrum for Wireless Transmission.

S. Pagadarai, R. Rajbanshi, G. J. Minden, A. M. Wyglinski. "Agile Transmission Techniques." in *Cognitive Radio Communications and Networks: Principles and Practice* (A. M. Wyglinski, M. Nekovee, Y. T. Hou (eds.)), Academic Press, 2009.

Existing Dynamic Spectrum Access Approaches

- ▶ *Spectrum Pooling*: Create a common inventory of spectral resources from licensed users
- ▶ Cooperative versus non-cooperative transmission
 - ▶ *Cooperative Transmission*: Exchange of information between users, centralized or non-centralized control, etc.
 - ▶ *Non-cooperative Transmission*: Minimum or no exchange of information, poor spectrum utilization efficiency, nodes act in a greedy fashion
- ▶ Underlay versus overlay transmission

Underlay Transmission Approach




Figure : Underlay Spectrum Sharing.

S. Pagadarai, R. Rajbanshi, G. J. Minden, A. M. Wyglinski. "Agile Transmission Techniques." in *Cognitive Radio Communications and Networks: Principles and Practice* (A. M. Wyglinski, M. Nekovee, Y. T. Hou (eds.)), Academic Press, 2009.

Overlay Transmission Approach




Figure : Overlay Spectrum Sharing.

S. Pagadarai, R. Rajbanshi, G. J. Minden, A. M. Wyglinski. "Agile Transmission Techniques." in *Cognitive Radio Communications and Networks: Principles and Practice* (A. M. Wyglinski, M. Nekovee, Y. T. Hou (eds.)), Academic Press, 2009.

Challenges

- ▶ What are the design issues that arise during secondary utilization of a licensed band?
 - ▶ Minimum interference to licensed transmissions
 - ▶ Maximum exploitation of the gaps in the time-frequency domain

NC-OFDM Transmitter




Figure : Non-contiguous OFDM Transmitter.

S. Pagadarai, R. Rajbanshi, G. J. Minden, A. M. Wyglinski. "Agile Transmission Techniques." in *Cognitive Radio Communications and Networks: Principles and Practice* (A. M. Wyglinski, M. Nekovee, Y. T. Hou (eds.)), Academic Press, 2009.

NC-OFDM Receiver




Figure : Non-contiguous OFDM Receiver.

S. Pagadarai, R. Rajbanshi, G. J. Minden, A. M. Wyglinski. "Agile Transmission Techniques." in *Cognitive Radio Communications and Networks: Principles and Practice* (A. M. Wyglinski, M. Nekovee, Y. T. Hou (eds.)), Academic Press, 2009.

OoB Interference Issue




Figure : An Illustration of the Interference Due to One OFDM-modulated Carrier.

OFDM Interference




Figure : An Illustration of the Interference in a BPSK-OFDM System with 16 Subcarriers.

Interference Solution 1: Windowing




Figure : Structure of the Temporal OFDM Signal Using a Raised Cosine Window.

S. Pagadarai, R. Rajbanshi, G. J. Minden, A. M. Wyglinski. "Agile Transmission Techniques." in *Cognitive Radio Communications and Networks: Principles and Practice* (A. M. Wyglinski, M. Nekovee, Y. T. Hou (eds.)), Academic Press, 2009.

Interference Solution 1: Windowing




Figure : Impact of Roll-off Factor on the PSD.

Interference Solution 2: Cancellation Subcarriers




Figure : Illustration of Sidelobe Power Reduction with Cancellation Subcarriers.

Interference Solution 3: Constellation Expansion




Figure : A Mapping of Symbols from QPSK Constellation to an Expanded Constellation Space.

Interference Solution 3: Constellation Expansion

- ▶ Map symbols from the original constellation space to an expanded one
 - ▶ Multiple symbols from the expanded constellation are associated with each symbol from the original constellation
- ▶ Exploit the randomness in choosing the symbols and consequently, their combination which leads to a lower sidelobe level compared to the original case

Non-contiguous Transmission Implementation

- ▶ In an NC-OFDM scenario, several OFDM subcarriers are turned OFF in order to avoid interfering with an incumbent user
- ▶ If the available spectrum is sparse, the number of zero-valued inputs to the FFT lead to an inefficient use of hardware




Figure : Subcarrier Distribution over Wideband Spectrum.

FFT Pruning




Figure : An 8point DIF FFT Butterfly Structure for a Sparse Input.