

Respiratory Protection



1

Objectives

- Principles of respiratory protection
 - History
 - Role
 - Regulations and guidance
 - Equipment
 - Fit Testing
 - Selection and use
 - Programs (WA State)

2

History

- Animal bladders used in Roman mines
- Atmosphere-supplying devices in 1700's
- Activated charcoal discovered (1854)
- World War I "Gas Masks"

3

Atmosphere-Supplying Respirators

- Atmosphere-supplying respirator technology was well developed by the 1700's



4

Tyndall and Shaw "Smoke Cap"




Figure 2.2
Tyndall and Shaw "smoke cap."



Figure 2.3
Tyndall and Shaw "smoke can" **5**

Respiratory protection

OSHA's general policy on respirator use:

- Where engineering or administrative controls are not feasible or insufficient
- During the time when engineering or administrative controls are being implemented
- For emergency response situations

6

Role in Exposure Control

- "Hierarchy of Controls"
 - PPE is the least desirable method of control
- Respirator use involves risk
 - Medical use determinations
- Administrative procedures
 - Written program
 - Qualified "program administrator"
- Many Limitations of respirators
 - Monitoring contaminant levels
 - Fit testing
 - Cost
 - Can leak, wear out, or be the wrong kind
 - Can be hot, uncomfortable and make it hard to see or talk
 - Can be hard to breathe through
 - They are easily removed in contaminated air

7

When Are Respirators Needed?

- In an oxygen-deficient atmosphere
- When "Permissible Exposure Limits" are exceeded
- When required by a pesticide label
- When needed for infection control
- When required by company policy

Normally, an oxygen deficiency will only be found in a confined space or a major chemical spill. There are only a few pesticides that have label requirements for respirators. Some employers require their employees to wear respirators as a safety precaution even though they may not be required due to a PEL.


8

Oxygen Deficiency

Oxygen deficiency can occur in confined or enclosed spaces, during fires or large chemical releases.

Normal air contains 21% oxygen. An area with oxygen content below 19.5 % is considered "oxygen deficient".

Only a supplied air respirator can protect against the effects of oxygen deficiency.



Regulations and Guidance

- **OSHA**
 - 29 CFR 1910.134, 1974, 1998
- **NIOSH**
 - 1976, 1987 "Guide to Industrial Respiratory Protection"
 - 1987 "Respirator Decision Logic"
 - 1995 "42 CFR 84"
- **WISHA**
 - WAC 296-842
- **ANSI STANDARDS**
 - Z88.2-1969, 1980, 1992 (Respiratory Protection)

10

OSHA's Respiratory Protection Program

1. Written program
2. Selection base on hazards involved
3. Operator training
4. Reserved (?)
5. Cleaning and disinfection of respirators
6. Storage of respirators
7. Inspection and maintenance of respirators
8. Surveillance of worker exposures
9. Regular evaluation of respirator program
10. Medical evaluation of respirator users
11. Use of approved respirators

11

Updated regulations

- NIOSH changes to respirator equipment approvals
- Substance specific standards sometimes contain unique requirements
- OSHA finalized new 1910.134 standard in 98
 - Consolidates other standards' requirements
 - Assigned Protection Factors (APF) in 2003/04
 - Some changes in medical qualifications (screening)
 - Fit testing (Quant) required for all tight-fitting respirators
 - Cartridge change out to be based on objective data
 - Respirator administrator required
 - TB respirators consolidated in 2003

12

OSHA Proposes Revised Respiratory Protection Standards

- The Occupational Safety and Health Administration published two proposed rules in the June 6 Federal Register to enhance worker protections from respiratory hazards on the job. OSHA is seeking comments until Sept. 4, 2003, on its proposals to amend the Respiratory Protection Standard to include a new fit testing procedure and incorporate new Assigned Protection Factors (APFs) for respiratory protection programs. The proposed rules are expected to prevent approximately 4,000 injuries and illnesses and prevent about 900 deaths annually from cancer and other chronic diseases.
- In a notice of proposed rulemaking, OSHA proposes to amend the existing Respiratory Protection Standard in order to incorporate Assigned Protection Factors (APFs) as part of a complete respiratory protection program to assist workers and employers in the proper selection of respirators. APFs are numbers that reflect the workplace level of respiratory protection that respirators are expected to provide to employees
- http://www.osha.gov/pls/oshaweb/owadisp.show_document?p_table=FEDERAL_REGISTER&p_id=13749

13

OSHA Respirator Standard

- Use engineering controls where feasible
- Employer supplies respirators and establishes a program
- Program must be written with work-site specific procedures and elements for required respirator use
- Program must have an administrator
- Medical evaluations
- Fit testing for tight-fitting respirators

14

OSHA Respirator Standard

- New procedures where respirator is worn voluntarily (program still required)
- Appropriate selection of respirators - NIOSH certification and within certification limits
- Evaluate exposures - assume IDLH if unable to evaluate
- Selection to include sufficient number...to get a good fit
- Change-out of cartridges – End of Service Life or “objective data”

15

OSHA Respirator Standard

Medical evaluations:

- By a “Physician or other licensed health care professional” (PLHCP)
- Screening questionnaire
- Follow-up examination if any positive answers
- Supply PLHCP with respirator info, work conditions, other PPE, duration and frequency of respirator use, copy of written program and OSHA standard
- Must supply PAPR if negative pressure respirator is unacceptable

16

OSHA Respirator Standard

Additional Medical evaluations required when:

- Report of related medical signs or symptoms
- PLHCP, supervisor or program administrator informs the employer that a reevaluation is needed
- Information from program, fit-testing suggest need for reevaluation
- Change in workplace increases physiological burden on worker

17

OSHA Respirator Standard

Fit testing:

- Qualitative or quantitative methods used for tight-fitting respirators
- Must be re-fitted when respirator changed *and* annually
- Qualitative can only be used with fit factors of 100 or less; quantitative required when $FF > 100$
- Must use methods in Appendix A
- Atmosphere-supplying respirator must be tested when in negative pressure mode

18

OSHA Respirator Standard

Other things ...

- No facial hair that can interfere with seal
- User seal test
- Cannot base cartridge change-outs on odor, smell or taste
- Seal check whenever donning respirator
- In IDLH areas, must have standby outside equipped and trained for rescuing
- Structural firefighting: 2 in and 2 out (buddy)

19

Specific Respiratory Protection Stds.

Abrasive Blasting WAC 296-24-07315
Acrylonitrile WAC 296-62-07326 see section (8)
Agriculture WAC 296-307-11010
WAC 296-307-12048 see section (3)(i)
Anhydrous Ammonia WAC 296-24-61009 see section (10)
Arsenic (inorganic) WAC 296-62-07347 see section (8)
Asbestos WAC 296-62-07315
Benzene WAC 296-62-07323 see section (7)
Beryllium (mining) WAC 296-24-71515
Butadiene WAC 296-62-07602 see section (8)
Cadmium (construction) WAC 296-155-174 see section (7)
Cadmium (general industry) WAC 296-62-07413
Cadmium (welding, general industry) WAC 296-24-71517
Carcinogens (general) WAC 296-62-07306
Coke Ovens WAC 296-62-20011
Concrete Finishing WAC 296-155-483 see section (4)
Cotton Dust WAC 296-62-14553 see section (8)
DBCP WAC 296-62-07343 see section (8)
Emergency Response WAC 296-824
Ethylene Oxide WAC 296-62-07367
Fire Brigades WAC 296-24-53515
Fire Fighters WAC 296-303-04001, WAC 296-303-02301 see section (15),
WAC 296-303-13001, WAC 296-303-09001, WAC 296-303-09003
Formaldehyde WAC 296-62-07540 see section (7)
Hazardous Waste Operations WAC 296-62-30220, WAC 296-62-31170
Lead (construction) WAC 296-155-17611
Lead (general industry) WAC 296-62-07321 see section (7)
Mercury (welding) WAC 296-24-71519
Methylene Chloride WAC 296-62-07470 see section (7)
Methylenedianiline (construction) WAC 296-155-17317
Methylenedianiline (general industry) WAC 296-62-07515
Preservative Coatings (welding) WAC 296-24-722 see section (3)(a)
Thiram WAC 296-62-07519 see sections (3)(c)(vi) & (x)
Tunnels & Shafts WAC 296-155-730 see section (7)
Vinyl Chloride WAC 296-62-07329 see section (7)

This is a list of the most frequently used standards with respiratory protection requirements, but it's not a complete list for all WISHA standards. While these requirements are viewed as being "supplemental" to the requirements specified in the main respiratory protection standard, WAC 296-62 Part E, they may, at times, preempt some of the requirements in the main standard if noted.

20

Respirator Equipment

21

Types of Respirators

Air-purifying respirators – filters air through cartridges or filtering facepieces (dust masks)

Powered air-purifying respirators – PAPP filters air through cartridges with assistance of a blower.

Airline respirators – provides unlimited clean air from a compressor.

Self-contained breathing apparatus (SCBA) – provides 30- 60 minutes of clean air from a tank.

Escape respirators – provides air for escape only from a small bottle.

22

Respirator Terminology

- Respiratory inlet covering
- Pressure relative to atmosphere
- Mode of operation

23

Respiratory Inlet Covering

- Definition
 - That portion of a respirator that forms the protective barrier between the user's respiratory tract and an air-purifying device or breathing air source, or both
 - ANSI Z88.2-1992
 - OSHA 1910.134 (1998)

24

Respiratory Inlet Covering

- **Mouthpiece**

- Used to escape from a contaminated atmosphere
- Noseclamps prevent inhaling through nostrils
- Acid-gas mouthpiece “escape” respirators (APR)
- “Self rescuer” APR
 - » CO catalyst “Hopcalite”
 - » Used to escape from mines
- Self-Contained Self Rescuer (SCSR)
 - » KO₂ absorbs CO₂ and releases O₂



25

Respiratory Inlet Covering

- **Quarter-Face**

- Extend bridge of nose to front of chin
- Popular in mining industry
- Replaceable filter element



26

Respiratory Inlet Covering

- **Half-Face**

- Bridge of nose to bottom of chin
- Variety of sizes
- Usually negative-pressure APR
- Filtering facepiece
 - » Avoid using non-NIOSH approved dust masks



27

Respiratory Inlet Covering

- **Full Facepiece**

- Better “fit” (and protection)
- Variety of sizes
- Eye protection
- Eyeglasses?
- “Dead Air” issues
 - » “Nosecup” recommended



28

Respiratory Inlet Covering

- **Hood/Helmet**

- “Loose fitting”
- Welding
- Abrasive Blasting “Type CE”



29

Operating Pressure

- **Negative pressure**
 - Pressure drops below atmosphere when user inhales
 - Less protective due to facepiece leaks
- **Positive pressure**
 - Pressure above atmosphere
- **Pressure Demand**
 - Elevated pressure at all times
 - Most protective - suitable for IDLH

30

Mode of Operation

- **Air-Purifying Respirators (APRs)**

- Contaminants removed from the air
 - » Filters for removing particulates
 - » Cartridges for removing gases or vapors - may have filters, too
 - » Canisters (used with “gas masks” -- large capacity)
 - » Oxygen must be > 19.5%
- Limited protection

- **Atmosphere-supplying respirators**

- Not limited by type of atmospheric hazard
- Suitable for oxygen deficiency or IDLH
- SCBA's
- Air line respirators (Type C or CE)
- Combinations of SCBA's and SAR's

31

Air Purifying Respirators

- **Respirator Types**

- Negative pressure
 - » Mouthpiece
 - » Quarter-, half-, full-facepiece
- Positive pressure
 - » Powered Air Purifying Respirator (PAPR)
 - » Less physiological stress,
 - » Specified in many OSHA standards
 - » Tight- or loose-fitting models
- Specialty respirators
 - » Escape (mouthpiece, “gas mask”)
 - » Welding



32

Some types of Air-purifying Respirators



Filtering facepiece (dust mask)



Half-face cartridge respirator



Full-face cartridge respirator



Powered air-purifying respirator

33

Aerosol removing respirators

Filters can remove dusts, mists, fumes, others
Cannot protect against gases, vapors, or low O₂

Removal mechanisms:

- interception
- sedimentation
- impaction
- diffusion
- electrostatic attraction

34

Nine filter types

- 3 levels of filter efficiency:
 - 95% (called “95”)
 - 99% (called “99”)
 - 99.97% (called “100”)
- 3 categories of resistance to filter efficiency degradation:
 - N (Not resistant to oil)
 - R (Resistant to oil)
 - P (oil Proof)

35

Selection of N, R, and P-series filters

- If no oil particles are present in the work environment, use a filter of any series.
- If oil particles are present, use an R- or P-series filter.
- If oil particles are present and the filter is to be used for more than one work shift, use only a P-series filter.
- Selection of filter efficiency depends on how much filter leakage can be accepted.
- Choice of face piece depends on level of protection needed (APF).

36

Gas and vapor removing respirators

Use sorbents

Housed in cartridges or canisters

Removal mechanisms:

- adsorption
- absorption
- chemisorption
- catalysis

Designed for specific contaminants or classes

37

Gas and vapor removing cartridges

Organic vapor cartridges:

- currently tested with CCl_4 at 1000 ppm (only)
- may or *may not* be very effective for specific vapors
- seek guidance from respirator manufacturer including test data on vapor in use
- only small amount of charcoal in cartridges
- more charcoal in canisters
- color code: black

38

Service life of cartridges or canisters

Depends on:

- quality and amount of sorbent
- packing uniformity and density
- exposure conditions, breathing rate
- relative humidity
- temperature
- contaminant concentration
- affinity of the gas or vapor for the sorbent
- presence of other gases and vapors

39

Acid gas respirators

- Designed for removing acidic gases
- Tested by NIOSH against chlorine, HCl and SO_2 (only)
- Limited to fairly low concentrations
 - Chlorine 10 ppm
 - Hydrogen chloride 50 ppm
 - Sulfur dioxide 50 ppm
- Color code: white

40

Alkaline gas cartridges

- Contains chemicals for removing alkaline gases such as:
 - ammonia
 - methylamine
- Concentrations limited
 - ammonia 300 ppm
 - methylamine 100 ppm
- Color code: green

41

Air-purifying respirators additional information

- Replace cartridges:
 - NIOSH: daily or after each use, or even more often if odor, taste, or irritation
 - some canisters may have end of service life indicators
- Other cartridges available:
 - pesticides
 - carbon monoxide
 - ethylene oxide
 - formaldehyde
 - hydrogen fluoride
 - hydrogen sulfide
 - mercury
 - phosphine
 - vinyl chloride

42

Colors for AP elements

- | | |
|-----------------------------------|----------|
| • Acid gas | white |
| • Organic vapors | black |
| • Ammonia gas | green |
| • Carbon monoxide | blue |
| • Acid gases and organic vapors | yellow |
| • Acid gas, ammonia, and OV | brown |
| • Acid gas, ammonia, CO, and OV | red |
| • Other vapors and gases | olive |
| • Radioactive materials (HEPA) | purple * |
| • Dusts, fumes, mists (non-radio) | orange * |

43

“Adequate warning properties”

NIOSH permits air purifying respirators only if the contaminant has adequate warning properties:

- *reliable* detection of the contaminant below the PEL by user's sense of smell, taste, or irritation
- only applies to gases and vapors -- not particulate
- Exception is if AP element has an ESLI.
- Remember that odor thresholds vary substantially from one individual to another

OSHA: respirator cartridge *changeout* based on odors or taste unacceptable (new standard)

44


Atmosphere-supplying respirators

- Self-contained breathing apparatus (SCBA)
 - Supplied Air Respirators or Air-line (called "Type C" or "Type CE")
 - hose can be up to 300 feet
 - 4 cfm required for tight-fitting mask, 6 cfm for hoods and helmets
 - available in demand, pressure demand, and continuous flow arrangements
 - Combination SCBA and SAR
- Must be supplied with Grade D breathing air, usually from bottles or compressors

45

Atmosphere-Supplying Respirators

- Self-Contained Breathing Apparatus (SCBA)
 - Pressure-demand, open circuit
 - » 30 to 60 minute duration
 - » 2216 or 4500 PSI
 - Demand (virtually obsolete)
 - Closed circuit "rebreather"
 - » Up to 4 hours duration
 - » Used for mine rescue, etc.
 - » O₂ from cylinder or generator
 - » CO₂ is absorbed



46


Self-contained breathing apparatus (2)

- Open-circuit type
 - bottled air from 2000 to 4500 psi typically
 - time from 15 min to 60 min typically
 - demand or pressure demand or continuous flow
 - can be combined with supplied air respirator
 - escape-only type available in 5, 7, 10 or 15 minute size
- Closed-circuit type (also called re-breathers)
 - could be either negative or positive pressure type
 - possible to "over breathe"
 - more complicated to maintain
 - requires more training
 - longer use period ... sometimes up to 4 hours

47

Atmosphere-Supplying Respirators


- Supplied Air Respirators (SAR)
 - Also known as "airline" respirators or "Type C"
 - Supplied with compressed air
 - » 4-6 CFM
 - Pressure of operation
 - » Pressure demand
 - » Demand
 - » Continuous flow
 - Combination
 - » APR
 - » SCBA (for IDLH)



48

Atmosphere-Supplying Respirators

- Air Quality "Grade D" minimum (1910.134)
- Compressor provisions for air quality
 - air intake location
 - dew point 10 F below ambient
 - sorbent bed and filters maintained
 - CO and/or high temperature alarm
 - incompatible fittings
- Cylinders maintained and tested
 - "Certificate of analysis", cylinders marked
 - -50 F dewpoint



49

Grade D Specifications

CGA G-7.1 Grade "D" (Compressed Gas Association)	
Oxygen	19.5 - 23.5%
Carbon Dioxide	1,000 ppm
Carbon Monoxide	10 ppm
Oil Mist	5 mg/m ₃
Odor	"no pronounced odor"

50

Sources of breathing air

- Compressors
 - Subject to failure
 - If oil-lubricated, can overheat changing oil mist into CO
 - Carbon vane type are available and oil-less
 - Can run continuously
 - Can be fitted with CO sensor and/or adsorption units
 - Air intake location is critical
- Compressed gas cylinders (breathing air)
 - Can be up to 3500 psi
 - Finite air supply...for limited time spans
 - Do not rely on utility services

51

Protection Factors

- **BREAK!**

52

Protection Factors

- **protection factor: $PF = C_o/C_i$**
 - O for outside the mask, I for inside the mask
- **Penetration efficiency is inversely related:**
 - Used to average PF values
$$P_e = \frac{1}{PF}$$
- **Fit factor is the PF observed during a quantitative fit test (usually only 5 to 10 min)**
- **Workplace protection factor (WPF)**
 - time up to 8 hours
 - the C_i value is the average contaminant value inside the respirator

53

Protection Factors

- “Protection factors” are related to the amount of contaminant that gets into a respirator
 - Generic PF = Conc. outside / conc. inside
- **Assigned Protection Factor (APF)**
 - Minimum anticipated protection for a specific type
 - Used to establish respirator safe use limits
 - Recommended by OSHA, 2003 (not addressed by 1910.134 in 1998)
 - Established by NIOSH, ANSI
- **Assigned protection factor APF (also called hazard ratio)**

$$\text{Assigned Protection Factor (APF)} \left[\text{Expected } \frac{C_o}{C_i} \right] \quad APF \geq \frac{C_{air}}{TLV}$$

54

NIOSH Assigned Protection Factor (APF)

Respirator type	APF
Quarter face	5
Half-face APR or "demand" supplied air	10
Hood or helmet PAPR or continuous flow	25
Full-Face APR or "Demand" supplied air, any tight-fitting facepiece PAPR or continuous	50
Half-face pressure demand	1000
Full-face pressure demand	2000
SCBA pressure demand	10000

55

Assigned Protection Factor (APF), from ANSI Z88.2-1992

Respirator type		Inlet covering			
		mask, 1/4 mask	full face-piece	Helmet, hood	Loose-fitting facepiece
Air purifying		10	100		
Powered Air Purifying		50	100 or 1000*	1000	25
Atmosphere supplying - Airline	Demand	10	100		
	Continuous flow	50	1000	1000	25
	Pressure-demand	50	1000	* 1000 APF for high-efficiency filters only	
Atmosphere supplying - SCBA	Demand	10	100		
	Pressure-demand		10000		

56

OSHA proposed Assigned Protection Factors	
Respirator type	APF
Quarter face	n.a.
Half-face APR or "demand" supplied air	10
Hood or helmet PAPR or continuous flow	1000
Loose-fitting facepiece PAPR or continuous flow	25
Full-Face APR or "Demand" supplied	50
Tight-fitting full-facepiece, PAPR or continuous flow	1000
Half-face pressure-demand	1000
Full-face pressure-demand	2000
SCBA pressure-demand	10,000

57

TABLE V-1.—SUMMARY RESULTS FROM WORKPLACE PROTECTION FACTOR (WPF) STUDIES AND ESTIMATED FREQUENCIES OF RESPIRATOR FAILURE, BASED ON A ONE-FACTOR ANOVA ANALYSIS OF DATA FROM WORKPLACE PROTECTION FACTOR (WPF) STUDIES							
Study	Geometric mean WPF (95% C.I.) ¹	Geometric standard deviation	Mean WPF	Estimated percent of workers with:			
				Mean WPF ≤ 10 ²	Mean WPF ≤ 1 ²	WPF ≤ 10 at least 5% of the time ³	WPF ≤ 1 at least 5% of the time ³
Studies Reflecting Inadequate Program Elements							
Particulate Exposure							
Toney and Barnhart (1972) (Ex. 64-68)	*11.4 (3.2-39.6)	4.12	31.1	78.8	9.0	100	60.4
Harris et al. (1974) (Ex. 27-11)	*3.9 (1-17.9)	*2.93	6.4	99.7	38.8	100	96.4
Low Estimate	*5.7 (1.6-20.4)	*2.83	10.2	97.9	12.5	100	82.3
High Estimate							
Weighted Geometric Mean	45.6						
Gas/Vapor Exposure							
Moore and Smith (1978) (Ex. 64-69)	15.29 (8.3-28.1)	12.36	22.1	36.2	<0.01	98.9	1.9
Respirator A							
Respirator B	13.72 (7.7-24.4)	12.16	18.4	41.3	<0.01	99.7	0.5
Respirator C	9.89 (4.8-19.2)	12.16	12.9	63.1	<0.01	100	9.5
Toney and Barnhart (1972) (Ex. 64-68)	*3.8 (1.2-11.9)	*2.28	5.3	100	14.7	100	95.7
Weighted Geometric Mean	16.4						
Studies Reflecting Good Program Elements							
Particulate Exposure							
Dixon and Nelson (1989) ⁴	3360 (3101-3649)	4.8	11,498	<0.01	<0.01	<0.01	<0.01
Calabrese and Bard (1989) ⁵	47 (31-72)	2.5	72	0.2	<0.01	30.1	<0.01
Leith and Campbell (1984) ⁶	169 (150-220)	3.8	405	0.1	<0.01	9.0	0.02
Holmes and Dixon (1988) ⁷	258 (192-347)	5.2	1004	0.7	<0.01	14.5	0.3
Cousins et al. (1986) ⁸	96 (75-122)	2.3	136	<0.01	<0.01	0.1	<0.01
Cotton and Mullins (1992) ⁹	147 (117-185)	2.5	224	<0.01	<0.01	0.1	<0.01
Myers (1992) ¹⁰	346 (266-468)	7.2	2,428	2.8	0.1	22.2	1.7
Weighted Geometric Mean	*142						
Gas/Vapor Exposure							
Gabriel et al. (1990) (Ex. 64-22)	78 (54-115)	3.5	173	1.1	<0.01	31.7	0.2

*100% confidence interval of the geometric mean WPF calculated as follows for simultaneous confidence intervals: $\pm 2SD \ln(10) \times \sqrt{1 - 0.05/n}$, where $n = 1 - (0.05/n)$.

²WPF is the number of WPF measures in each study and n is the number of studies being compared (i.e., 10 for particulate studies and 5 for gas/vapor studies).

³Calculated from equation 1 as described in the text: $3.1 \times 10^4 \times WPF \times 10^{-4} \times 0.5 \times 0.5 \times WPF^2 = 2$.

⁴Calculated by OSHA from an unpublished data presented by the authors.

⁵Calculated by OSHA from unpublished data presented by the authors.

⁶Calculated by OSHA from unpublished data presented by the authors.

⁷Calculated by OSHA from unpublished data presented by the authors.

⁸Calculated by OSHA from unpublished data presented by the authors.

⁹Calculated by OSHA from unpublished data presented by the authors.

¹⁰Calculated by OSHA from unpublished data presented by the authors.

¹¹Calculated by OSHA from unpublished data presented by the authors.

¹²Calculated by OSHA from unpublished data presented by the authors.

¹³Calculated by OSHA from unpublished data presented by the authors.

¹⁴Calculated by OSHA from unpublished data presented by the authors.

¹⁵Calculated by OSHA from unpublished data presented by the authors.

¹⁶Calculated by OSHA from unpublished data presented by the authors.

¹⁷Calculated by OSHA from unpublished data presented by the authors.

¹⁸Calculated by OSHA from unpublished data presented by the authors.

¹⁹Calculated by OSHA from unpublished data presented by the authors.

²⁰Calculated by OSHA from unpublished data presented by the authors.

²¹Calculated by OSHA from unpublished data presented by the authors.

²²Calculated by OSHA from unpublished data presented by the authors.

²³Calculated by OSHA from unpublished data presented by the authors.

²⁴Calculated by OSHA from unpublished data presented by the authors.

²⁵Calculated by OSHA from unpublished data presented by the authors.

²⁶Calculated by OSHA from unpublished data presented by the authors.

²⁷Calculated by OSHA from unpublished data presented by the authors.

²⁸Calculated by OSHA from unpublished data presented by the authors.

²⁹Calculated by OSHA from unpublished data presented by the authors.

³⁰Calculated by OSHA from unpublished data presented by the authors.

³¹Calculated by OSHA from unpublished data presented by the authors.

³²Calculated by OSHA from unpublished data presented by the authors.

³³Calculated by OSHA from unpublished data presented by the authors.

³⁴Calculated by OSHA from unpublished data presented by the authors.

³⁵Calculated by OSHA from unpublished data presented by the authors.

³⁶Calculated by OSHA from unpublished data presented by the authors.

³⁷Calculated by OSHA from unpublished data presented by the authors.

³⁸Calculated by OSHA from unpublished data presented by the authors.

³⁹Calculated by OSHA from unpublished data presented by the authors.

⁴⁰Calculated by OSHA from unpublished data presented by the authors.

⁴¹Calculated by OSHA from unpublished data presented by the authors.

⁴²Calculated by OSHA from unpublished data presented by the authors.

⁴³Calculated by OSHA from unpublished data presented by the authors.

⁴⁴Calculated by OSHA from unpublished data presented by the authors.

⁴⁵Calculated by OSHA from unpublished data presented by the authors.

⁴⁶Calculated by OSHA from unpublished data presented by the authors.

⁴⁷Calculated by OSHA from unpublished data presented by the authors.

⁴⁸Calculated by OSHA from unpublished data presented by the authors.

⁴⁹Calculated by OSHA from unpublished data presented by the authors.

⁵⁰Calculated by OSHA from unpublished data presented by the authors.

⁵¹Calculated by OSHA from unpublished data presented by the authors.

⁵²Calculated by OSHA from unpublished data presented by the authors.

⁵³Calculated by OSHA from unpublished data presented by the authors.

⁵⁴Calculated by OSHA from unpublished data presented by the authors.

⁵⁵Calculated by OSHA from unpublished data presented by the authors.

⁵⁶Calculated by OSHA from unpublished data presented by the authors.

⁵⁷Calculated by OSHA from unpublished data presented by the authors.

⁵⁸Calculated by OSHA from unpublished data presented by the authors.

⁵⁹Calculated by OSHA from unpublished data presented by the authors.

⁶⁰Calculated by OSHA from unpublished data presented by the authors.

⁶¹Calculated by OSHA from unpublished data presented by the authors.

⁶²Calculated by OSHA from unpublished data presented by the authors.

⁶³Calculated by OSHA from unpublished data presented by the authors.

⁶⁴Calculated by OSHA from unpublished data presented by the authors.

⁶⁵Calculated by OSHA from unpublished data presented by the authors.

⁶⁶Calculated by OSHA from unpublished data presented by the authors.

⁶⁷Calculated by OSHA from unpublished data presented by the authors.

⁶⁸Calculated by OSHA from unpublished data presented by the authors.

⁶⁹Calculated by OSHA from unpublished data presented by the authors.

⁷⁰Calculated by OSHA from unpublished data presented by the authors.

⁷¹Calculated by OSHA from unpublished data presented by the authors.

⁷²Calculated by OSHA from unpublished data presented by the authors.

⁷³Calculated by OSHA from unpublished data presented by the authors.

⁷⁴Calculated by OSHA from unpublished data presented by the authors.

⁷⁵Calculated by OSHA from unpublished data presented by the authors.

⁷⁶Calculated by OSHA from unpublished data presented by the authors.

⁷⁷Calculated by OSHA from unpublished data presented by the authors.

⁷⁸Calculated by OSHA from unpublished data presented by the authors.

⁷⁹Calculated by OSHA from unpublished data presented by the authors.

⁸⁰Calculated by OSHA from unpublished data presented by the authors.

⁸¹Calculated by OSHA from unpublished data presented by the authors.

⁸²Calculated by OSHA from unpublished data presented by the authors.

⁸³Calculated by OSHA from unpublished data presented by the authors.

⁸⁴Calculated by OSHA from unpublished data presented by the authors.

⁸⁵Calculated by OSHA from unpublished data presented by the authors.

⁸⁶Calculated by OSHA from unpublished data presented by the authors.

⁸⁷Calculated by OSHA from unpublished data presented by the authors.

⁸⁸Calculated by OSHA from unpublished data presented by the authors.

⁸⁹Calculated by OSHA from unpublished data presented by the authors.

⁹⁰Calculated by OSHA from unpublished data presented by the authors.

⁹¹Calculated by OSHA from unpublished data presented by the authors.

⁹²Calculated by OSHA from unpublished data presented by the authors.

⁹³Calculated by OSHA from unpublished data presented by the authors.

⁹⁴Calculated by OSHA from unpublished data presented by the authors.

⁹⁵Calculated by OSHA from unpublished data presented by the authors.

⁹⁶Calculated by OSHA from unpublished data presented by the authors.

⁹⁷Calculated by OSHA from unpublished data presented by the authors.

⁹⁸Calculated by OSHA from unpublished data presented by the authors.

⁹⁹Calculated by OSHA from unpublished data presented by the authors.

¹⁰⁰Calculated by OSHA from unpublished data presented by the authors.

¹ 95% confidence interval of the geometric mean WPF calculated as follows for simultaneous confidence intervals: $\pm 1.96 \ln(1 - 0.025)^{1/N}$, where N is the number of WPF measurements in each study and N is the number of studies being compared (i.e., 10 for particulate studies and 3 for gas/vapor studies).
² While n is the number of WPF measurements in each study and N is the number of studies being compared (i.e., 10 for particulate studies and 3 for gas/vapor studies).
³ Calculated from equation 10 as described in the text: $x = 0.1$ for WPF = 10, $x = 0.5$ for WPF = 2.
⁴ Calculated by OSHA from raw data presented by the authors.
⁵ Range of WPF values estimated by Popendorf (1989) (Ex. 64-512), from effective protection factor values (EPF) reported by Harris et al. (1974).
⁶ GEDs calculated by OSHA from median and mean EPF values reported by Harris et al.
⁷ Calculated as a weighted geometric mean as follows: $\exp((250 \times \ln(1004) + 150 \times \ln(14.5)) / 2)$.
⁸ Calculated by OSHA from median and mean WPF values reported by Moore and Smith.
⁹ Studies reviewed by Nelson (1995) (Ex. 64-514).

Protection Factors	
• Fit Factor	– Measured during fit testing procedures
Quantitative Fit Factor (QNFF)	$\left[\frac{C_o}{C_i} \right]$
• Workplace Protection Factor	– Measured under workplace conditions
Workplace Protection Factor (WPF)	$\left[\frac{C_o}{C_i} \right]$

59

Protection Factors	
• Effective protection factor	– Includes times when the worker is not wearing the respirator
Effective Protection Factor (EPF)	$\left[\frac{C_o}{C_{inhalated}} \right]$
– over unspecified length of time	
– supposed to represent total protection afforded worker including times worn and not worn.	
– Used in OSHA's lead standard	
• Program protection factor	– sometimes used with lead aerosols

60

Maximum Use Concentration

- **Maximum Use Concentration, MUC**
 - Not currently defined by OSHA, although many standards incorporate the general principle
 - Usually defined as the PEL x APF
 - must not be > IDLH or in excess of the cartridge limits
 - Based on several factors: APF, IDLH concentrations, and regulatory limits
- **Example**
 - » APF for half mask = 10
 - » PEL for lead = 0.05 mg/m³
 - » MUC = 10 x 0.05 mg/ = 0.5 mg/m³

61

RESPIRATOR FIT

- **User “seal checks” (formerly “fit checks”)**
 - Each time the respirator is worn
 - Positive- and negative-pressure (OSHA)
 - Odorous or irritant agents may be used (ANSI)
- **Fit Testing**
 - Formal test, to select respirator sizes and models
 - » Involves several “exercises”
 - » Initial fit testing, before the respirator is issued
 - » Repeated annually
 - Subject is exposed to a challenge atmosphere
 - » Qualitative tests (taste, odor, irritation)
 - » Quantitative tests (instrumentation)

62

Fit Testing Requirements

- **Previously, OSHA only required fit testing for negative pressure respirators**
- **Since 1998, all tight-fitting respirators must be fit tested**
 - Negative pressure respirators
 - » Qualitative testing for half-face
 - » Quantitative testing for full-face (where 500 FF is desired)
 - Positive pressure respirators
 - » Must be tested in the negative-pressure mode
 - Modify respirator for negative pressure operation, or use a “surrogate” respirator
 - » Quantitative or qualitative testing is acceptable

63

Fit testing

- **Qualitative fit testing (QLFTs)**
 - isoamyl acetate (IAA)
 - irritant smoke (usually titanium and stannic chloride)
 - saccharin aerosol (taste test)
 - denatonium benzoate (Bitrex)
 - must verify wearer can respond
 - wearer must be truthful
- **Quantitative fit testing (QNFTs)**
 - dioctyl phthalate aerosol (DOP)
 - corn oil
 - sodium chloride
 - DEHS
 - ambient air (with submicron particulate counting)
 - ambient air (pressure differential)

64

Qualitative Fit Testing

- OSHA accepts 4 qualitative protocols
 - Isoamyl acetate (banana oil)
 - Saccharine
 - Bitrex
 - Irritant smoke
- Outcome depends on subject's response
 - Strong subject incentive to "pass" the test
 - Results may not be reliable
- Pass criteria is based on 100 Fit Factor
 - This provides a 10x safety factor for APF 10

65

Qualitative Fit Testing

- Saccharine
 - Particulate filter APRs, including dust masks
 - Hood
 - Sensitivity test
 - Challenged with 100 x solution
- Bitrex
 - Denatonium benzoate
 - Same equipment



66

Qualitative Fit Testing

- Isoamyl Acetate (IAA, "banana oil")
 - Sensitivity test
 - APRs with organic vapor cartridges
 - IAA saturated paper towel inside hood
- Irritant smoke (stannic chloride)
 - Not for persons with asthma!
 - No hood or enclosure
 - APR with high-efficiency filters
 - Safety concerns



Quantitative Fit Testing

- Quantitative fit testing uses probed respirators (or adapters) to measure inside the facepiece
- "Fit factor" is determined from the leak rate.
 - Previously, fit testing was used to determine a "Personal protection factor" (ANSI 1980)
 - Now, criteria includes a 10x safety factor (ANSI 1992, OSHA)
 - » Measured Fit Factor must be at least 10x the Assigned Protection Factor to accept a facepiece



68

Quantitative Fit Testing

- OSHA accepts 3 quantitative protocols
 - Generated aerosol method
 - » Old technology
 - Condensation Nuclei Counter (CNC)
 - » Ambient air challenge atmosphere
 - Controlled negative pressure
 - » Measures actual leakage



Quantitative Fit Testing

- Fit factor calculations
 - Fit factors for each exercise are combined

$$\text{Overall Fit Factor} = \frac{\text{Number of exercises}}{1/ff_1 + 1/ff_2 + 1/ff_3 + 1/ff_4 + 1/ff_5 + 1/ff_7 + 1/ff_8}$$

Where ff_1 , ff_2 , ff_3 , etc. are the fit factors for exercises 1, 2, 3, etc.

70

Respirator selection

Routine use vs non-routine use

Workplace hazards

Physical characteristics

Physical demands of the work

Respirator capabilities and limitations

71

Selection: Exposure assessments

- Identify airborne contaminants where possible
- Match up specifications and limitations of respirators
- Consider abnormal conditions that may cause concentrations to rise
- Think in terms of “worst case” exposures
- Apply substance-specific requirements
- Communicate information to employees; discuss signs, symptoms of overexposure
- Keep good records

72

Determining physical state of airborne contaminant

Listing of contaminant in TLV book is a clue but there are some exceptions

Guidelines for estimating airborne phase have been developed based on:

- identity of the major constituents
- saturated vapor concentrations of constituents
- estimate of total airborne mass concentration
(the saturated vapor concentration and total airborne concentration can help predict phase)

73

Selection: Non-routine use of respirators

Three situations require careful consideration:

- entry into confined spaces
- entry into oxygen-deficient atmospheres
- emergencies

IDLH

ANSI: "...any atmosphere that poses an immediate, irreversible debilitating effects on health..." (acute effects vs chronic exposures)

OSHA standard requires atmospheres to be considered IDLH unless shown otherwise

74

Selection: IDLH, continued

NIOSH: IDLH based on two factors:

- worker must be able to escape within 30 min without losing life or suffering permanent health damage, and
- worker must be able to escape without severe eye or respiratory irritation or other reactions that could inhibit escape

also, atmospheres > LEL are IDLH

75

Respirator Selection

Conditions	Type of Respirator
IDLH conditions or oxygen deficiency	SCBA or airline respirator with escape bottle
Dust/chemical levels up to 1000 times PEL	Airline respirator with full facepiece or hood
Dust/chemical levels up to 100 times PEL	Air-purifying respirator with full facepiece
Dust/chemical levels up to 50 times PEL	Powered air purifying respirator with half facepiece
Dust/chemical levels up to 10 times PEL	Air-purifying respirator with half facepiece

76

NIOSH respirator decision logic

IDLH atmospheres -- Only 2 types allowed:

- SCBA in pressure-demand mode (≥15 minute air supply)
- Type C airline respirator, pressure-demand or continuous flow mode, with auxiliary escape bottle (minimum service life of 3 minutes)

IDLH atmospheres (low oxygen)

- Can use demand (negative pressure) airline respirator

77

Respirator Approval

- Respirators approved by NIOSH
 - Previously NIOSH/MSHA (30 CFR part 11)
 - NIOSH 42 CFR 84, since 1995
- Manufacturers submit respirators to NIOSH
- Each respirator configuration is approved
 - Includes:
 - » Airline hose diameter and length (up to 300 ft.)
 - » Air pressure (up to 125 psi)
 - » Cartridges
 - Any change voids the approval
- NIOSH Certified Equipment List
 - Previous documents contained useful information
 - Current document is little more than a list of manufacturers and approval numbers
 - <http://www.cdc.gov/niosh/celpamp.html>

78

NIOSH/MSHA certification

- Testing and certification codes issued (TC #)
- NIOSH personnel do actual testing
- List of approved respirators published

- | | |
|-----------------------|-----------------|
| • TC 13F + 2-3 digits | SCBA |
| • TC 14G + 2-3 digits | AP gas mask |
| • TC 19C + 2-3 digits | SAR |
| • TC 21C + 2-3 digits | Particulate AP |
| • TC 23C + 2-3 digits | Gas or vapor AP |

79

What is required in a respirator program?

- ✓ Respirator program administrator
- ✓ Written procedures and records
- ✓ Proper respirator selection
- ✓ Medical evaluation of respirator users
- ✓ Fit-testing of respirators to each user
- ✓ Respirator maintenance, repair & storage
- ✓ Assured air quality for supplied-air respirators
- ✓ Employee training


80

Written Respirator Program

Prepared materials:

- from manufacturers
- From WISHA sample program
- Other boiler plate programs

Must be workplace-specific



[Link to sample written respirator program](#)

Much of your written program can be composed of compiled procedures from several sources. But some procedures will need to reflect your specific workplace practices. Be careful of "boiler plate" programs which may not describe your workplace's selection considerations or its specific emergency procedures. The purpose of a written procedure is to get a specific, consistent outcome by giving instructions that can be applied in your actual work area.

81

Voluntary Respirator Use

If you allow employees to wear respirators:

- Provide the mandatory handout (link below),
- ensure safe use,
- provide medical evaluations
- ensure proper cleaning, storage and maintenance


http://www.lni.wa.gov/wisha/rules/generaloccupationalhealth/HTML/62E_1.htm#WAC296-62-07117

These requirements apply to voluntary use of all respirators including dust masks. Fit-testing is not required.

82

WISHA Respirator Regulations

WAC 296-842.




<http://www.lni.wa.gov/wisha/Rules/respirators/default.htm>

83

What type of respirator is this?

- "Nose Filters"
- <http://nosefilters.com/prod01.htm>



84



MACBETH'S WITCHES COMPLY TO OSHA STANDARDS

85