Functional Requirements vs. Design Parameters	Design Parameters													
Your project title here														Г
Team Members:				l	l		1			1				i
										l				l
														i
	11													ı
				1										ı
Template #4 Revised 1/7/02 by AMM				l		·	Ì							ı
Template #4 Revised 1/1/02 by Alvilvi] [l										i
			ł											ı
				l						l				ı
	1									1				ı
						:	İ							ı
				l										ı
				•				i						i
	1		i	1						l				ı
				1										l
														ı
										l .				i
														l
					1					l				ı
					l					ł				ı
Functional Requirements					1					l				
Tanonoma requirements	-	-	⊢		┝	ļ				 				⊢
			1							1				ı
			\vdash			\vdash				\vdash	 	_		┢╾
												1		i
		ļ	<u> </u>											
	l	1				ł				l				ĺ
		 	-		<u> </u>		_			<u> </u>	<u> </u>			
		1												l
		1	┢─	_	-	-				 		_		⊢
		İ								l				i
			-		\vdash					 				\vdash
		ŀ	1											l
			<u> </u>									1		
														Г
				<u> </u>	<u> </u>	L	ldash	<u></u>		<u> </u>		<u> </u>	L	
			1		l	1				1				
			<u> </u>	 	<u> </u>		\vdash			<u> </u>	ļ	<u> </u>		⊢
	ł		1		l					l				ı
		 	\vdash	-	 	-	\vdash			├			\vdash	\vdash
			l		l					l				ı
		1		t	T		\vdash		\vdash	\vdash	 		-	_
			1											ı
					T -									\vdash
	1	1	I		ı		1 :			ı	1			1

Figure xx: Functional Requirements vs. Design Parameters. The above table shows a matrix with rows consisting of the Functional Requirements and columns consisting of Design Parameters. The "X" denotes those areas in which Functional Requirements correlate strongly with Design Parameters.